



LL20FS020

LINEAR LOW DENSITY POLYETHYLENE FILM EXTRUSION GRADE

LL20FS020 is a Butene Comonomer based (LLDPE) with optimum levels of antioxidant, antiblocking agent & slip additives. The grade is designed to make blown film for general purpose application & blending with LDPE.

Typical Characteristics*			
Property	Test Method	Unit	Typical Value**
Melt Flow Index (190°C/2.16 kg)	ASTM D1238	gm/10 min	2.0
Density (23°C)	ASTM D1505	gm/cm ³	0.920
Tensile Strength at Break (MD/TD)	ASTM D882	Kg/cm ²	300/250
Elongation at Break (MD/TD)	ASTM D882	%	800/950
Tear Strength (MD/TD)	ASTM D1922	gm/25 μm	2.5/7.4
Dart Drop Impact (F-50)	ASTM D1709/A	g/μm	2.25

* Typical values not to be taken as specification

** Typical values (Mechanical) with 40μ film made with 1.8mm die gap & 2.25 BUR

Applications

Slip, Anti-block grade for general purpose film blending, carrier bags.

Regulatory Information

- Meets the requirements stipulated in standard IS : 10146 on "Specification for Polyethylene for safe use in contact with foodstuffs, pharmaceuticals, and drinking water". It also conforms to the positive list of constituents as prescribed in IS : 10141. The grade and the additives incorporated in it also comply with the FDA:CFR Title 21, 177.1520, Olefin polymers.

Storage Recommendations

- Bags should be stored in dry / closed conditions at temperatures below 50°C and protected from UV / direct sunlight.